

Rhino® FIX-A-TILE NTA SUPER Grey Cementitious Adhesive For Fixing Ceramic Tiles For Thin Bed Applications Develops High Efficiency, High Strength And High-Quality.

Description

Rhino Fix-A-Tile NTA Super is polymer modified, grey cement-based tile adhesive suitable for fixing tiles with less than 3% porosity, like vitrified, semi-vitrified tiles and natural stones on walls and floor in interior and exterior situations. Rhino Fix-A-Tile NTA Super is cementitious material in the powder form composed of cement, sand, polymer which needs on site addition of water to make a mortar which is used for fixing tiles over any cementitious surface.

Features / Advantages

- No shrinkage
- Increase productivity
- No curing required
- Highly water resistant
- No need for hacking
- Excellent adhesion to base plaster/ concrete surface
- It does not shrink or crack while curing
- Resistant to dilute acids, alkalis and soap water
- Consistent work quality
- High Durability
- Negligible waste
- Save time

Typical application

- Cement based backgrounds
- Cement plaster
- Cement concrete
- For dry area applications only
- Suitable for internal/ external floors applications
- Can be used for new/ old walls and tile on tile application

Technical Analysis (TYPE I: Conforms TO IS 15477:2019)

Technical Information

Property	Results
Colour	Grey dry powder
Spreadability	Spread easily with good notchability
Open Time	> 5 minutes
Adjustibility	> 5 minutes
Slip Resistance	> 0.5 mm
Pot Life	> 30 minutes
Density	1.5 -1.9 g/ml
Tensile Adhesion Strength (After 28 Days) Dry Condition	> 1.0 N/mm2
Tensile Adhesion Strength (After 28 Days) Wet Condition	> 1.0 N/mm2
Share Adhesion Strength (After 28 Days) Dry Condition	> 1.25 N/mm2
Share Adhesion Strength (After 28 Days) Dry Condition	> 1.0 N/mm2
Share Adhesion Strength (After 28 Days) Heat Aging Condition	> 1.0 N/mm2

Methods of Application

Surface Preparation

- Clean loose particles, dirt, grease and traces of foreign materials from the surface, if necessary, by using wire brush/sand paper or by chipping.
- For loose plaster areas or floors/wall which are not even, then remove the defective material and re-plaster the area with Ready-Mix Plaster to make them even.

Rhino® FIX-A-TILE NTA SUPER Grey Cementitious Adhesive For Fixing Ceramic Tiles For Thin Bed Applications Develops High Efficiency, High Strength And High-Quality.

Mixing

- Take approx. 200-300 ml of clean water for 1 Kg Rhino Fix-A-Tile NTA Super in a clean bucket. It is very important that add material into water and not vice versa.
- Stir continuously for 3-5 minutes by using mechanical stirrer or by hand to obtain a homogeneous lump-free paste.
- Allow the resultant paste to stand for about 10 minutes for the additives to dissolve.
- Re-mix again for about 2 Minutes. The mixture is now ready to apply.

Application

- Dampen the surface to be plastered with clean water. Allow excess water to drain off.
- The tiles should be immersed in water for about two hours before fixing.
- Apply the material on the substrate, use 6 mm notched trowel for application.
- Application should be angled between 35 to 45 degrees, using the right amount of pressure. Check for holes and gaps in the adhesive, spread it evenly.
- Fix the tile in the place and tap gently with wooden hammer. Using a notched trowel remove excess mixture from the tile and clean it by using a damp cloth or sponge.

Usage Precautions

- Do not add more water than recommended.
- Applicable for ceramic tiles only.
- Maximum thickness should not more than 3 mm.
- Do not used on gypsum plaster surface, paint, wood and metal.



Packing

25 Kg



Consumption

2 - 3 Sq. Ft./kg at 3 mm thickness on plain surface (or Depending on substrate conditions)



Cleaning of Tools & Equipments

Rhino Fix-A-Tile NTA Super should be removed from the tools at the earliest before it hardens, by cleaning with water.



Storage and Shelf life

- Store in cool, dry, and well-ventilated place away from heat source or direct sunlight.
- Keep away from water and damp area.
- Avoid using partially used material; open bags with partially used material should be kept in a bag with its mouth tied tightly with string to prevent lump formation.
- As temperature, humidity, water addition and other parameters vary from site to site; the above information should be treated as general guidelines.
- Shelf life is 12 months.

Ecology, Health and Safety

Health & Safety instructions, all chemicals should not come in contact with skin and eyes or be swallowed. Protective gloves and goggles should be worn.

If contact with skin occurs, wash well with soap and water.

Eye contamination should be washed thoroughly with clean water and medical advice sought. If swallowed seek medical attention immediately. Do not induce vomiting.

Rhino® FIX-A-TILE NTA SUPER Grey Cementitious Adhesive For Fixing Ceramic Tiles For Thin Bed Applications Develops High Efficiency, High Strength And High-Quality.

Disclaimer

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product.

Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions.

The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.

Mahafix

WATERPROOFING SPECIALIST



Nikhil Adhesives Limited

902, 9th Floor, A Wing, Kaledonia HDIL Building, Sahar Road, Opp. D-Mart,
Andheri (East), Mumbai – 400069



8655691400



support.mahafix@nikhiladhesives.com



www.nikhiladhesives.com

